


Manual for using Simos 8 ECU probe with ByteShooter. - Page 1




1. Description: This adaptor set can be used for unlocking Simos 8 ECU`s. It fits in most BDM positioning frames. Included in the kit is the Simos 8 probe and an ECU adaptor cable.

There is no need for soldering to the ECU at all!

2. Handling and adjustment:

Adaptor Cable Overview



A = Connect to ECU

B = Connect to ByteShooter OBD Cable

C = Connect to 12V Power Supply

Manual for using Simos 8 ECU probe with ByteShooter. - Page 2

Place the probe into the BDM frame retaining bracket and tighten the screws. Attach the ByteShooter tool to the ECU cable connection **B**, and connect the plug **A** to the ECU.




If lighting is required you can connect a 12V power supply to the jack on the probe (this only powers the LED's and not the ECU).

Adjust the ECU on the frame and move the retainer carefully towards the ECU, ensure that all the pins are in their designated position. A diagram showing the location of the connections can be found on page 3.


It is very important, that the retainer is free from backlash and moves smoothly!

You can now connect a power supply to the ECU cable connection **C** and proceed to unlock the ECU!



3. Disconnecting: To safely disconnect the probe from the ECU, you must first remove the power supply! Once disconnected it is safe to lift the frame and probe away from the ECU.

4. Programming the ECU: Once unlocked you can program the flash memory from OBD.



The pads marked in red have to make contact with the probe .

Technical alterations reserved!

Copyright by www.chiptuningshop.co.uk

This product should be operated by competent personnel only. Chiptuningshop Ltd do not accept any responsibility for damages, direct or consequential caused by improper handling.